

SAFETY DATA SHEET

Mixxit Toilet Cleaner

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Mixxit Toilet Cleaner

▼ Product no.

MXX619

Unique formula identifier (UFI)

JJA1-90RN-300M-7SKG

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Cleaning product

Restricted to professional users.

Product code (A.I.S.E.)

Code

AISE-P305 / Sanitary cleaner. Manual process.

Use descriptors (REACH)

Product category	Description
PC 35	Washing and Cleaning Products (including solvent based products)

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Cleenol Group Ltd.

Neville House, Beaumont Road, Banbury, Oxon,

OX16 1RB

United Kingdom

Tel: +44(0) 1295 251 721

www.cleenol.com

E-mail

technical.enquiries@cleenol.co.uk

Revision

20/09/2023

SDS Version

1.0

Date of previous version

18/08/2023 (1.0)

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.

Skin Corr. 1B; H314, Causes severe skin burns and eye damage.

Eye Dam. 1; H318, Causes serious eye damage.

Aquatic Acute 1; H400, Very toxic to aquatic life.

CLEENOL

For a cleaner, safer world

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Aquatic Chronic 2; H411, Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Flammable liquid and vapour. (H226)

Causes severe skin burns and eye damage. (H314)

Very toxic to aquatic life with long lasting effects. (H410)

Precautionary statement(s)

General

-

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)

Wear eye protection/protective gloves/protective clothing. (P280)

Do not breathe vapour/mist. (P260)

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. (P305+P351+P338)

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. (P303+P361+P353)

Storage

-

Disposal

Dispose of contents/container in accordance with local regulation (P501)

Hazardous substances

2,2'-(octadec-9-enylimino)bisethanol

Additional labelling

UFI: JJA1-90RN-300M-7SKG

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Citric Acid Monohydrate	CAS No.: 5949-29-1 EC No.: 611-842-9 UK-REACH: Index No.:	15-25%	Eye Irrit. 2, H319	
2,2'-(octadec-9-enylimino)bisethanol	CAS No.: 25307-17-9 EC No.: 246-807-3 UK-REACH: Index No.:	15-25%	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	
ethanol	CAS No.: 64-17-5 EC No.: 200-578-6 UK-REACH: Index No.: 603-002-00-5	10-15%	Flam. Liq. 2, H225	

CLEENOL

For a cleaner, safer world

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Sodium p-cumenesulphonate	CAS No.: 15763-76-5 EC No.: 239-854-6 UK-REACH: Index No.:	5-10%	Eye Irrit. 2, H319
---------------------------	---------------------------------------------------------------------	-------	--------------------

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Flush exposed area with water for a long time - at least 30 minutes. It may be necessary to flush for several hours. Use a comfortable water temperature (20-30 °C). Contact Poison Information/doctor/hospital for further advice on follow-up and treatment.

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes with plenty of water or salt water (20-30 °C) for at least 30 minutes and continue until irritation stops. Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.

Ingestion

In the case of ingestion, contact a doctor immediately. If the person is conscious, give them water. DO NOT try to induce vomiting unless this is recommended by a doctor. Hold head facing down to prevent vomit from returning to the mouth and throat. Prevent shock by keeping the injured person warm and calm. Initiate immediate resuscitation if breathing stops. If unconscious, roll the injured person into recovery position. Call an ambulance.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are

exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

- Sulphur oxides
- Nitrogen oxides (NO_x)
- Carbon oxides (CO / CO₂)
- Some metal oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Keep only in original packaging.

Storage temperature

6 - 40°C

Dry, cool and well ventilated

Incompatible materials

Combustible materials

Bases

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethanol

Long term exposure limit (8 hours) (ppm): 1000

Long term exposure limit (8 hours) (mg/m³): 1920

Diphenyl ether

Long term exposure limit (8 hours) (ppm): 1

Long term exposure limit (8 hours) (mg/m³): 7

Short term exposure limit (15 minutes) (ppm): 2

Short term exposure limit (15 minutes) (mg/m³): 14

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

2,2'-(octadec-9-enylimino)bisethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	150 µg/kgbw/day
Long term – Systemic effects - Workers	Dermal	420 µg/kgbw/day
Long term – Systemic effects - General population	Inhalation	522 µg/m ³
Long term – Systemic effects - Workers	Inhalation	2.96 mg/m ³
Long term – Systemic effects - General population	Oral	150 µg/kgbw/day

Diphenyl ether

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	25 mg/kg bw/day
Long term – Local effects - Workers	Inhalation	7 mg/m ³
Long term – Systemic effects - Workers	Inhalation	59 mg/m ³
Short term – Local effects - Workers	Inhalation	14 mg/m ³

ethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	206 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	343 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	114 mg/m ³
Long term – Systemic effects - Workers	Inhalation	380 mg/m ³
Short term – Local effects - General population	Inhalation	950 mg/m ³
Short term – Local effects - Workers	Inhalation	1900 mg/m ³
Long term – Systemic effects - General population	Oral	87 mg/kg bw/day

Sodium p-cumenesulphonate

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Dermal	48 µg/cm ²
Long term – Local effects - Workers	Dermal	96 µg/cm ²
Long term – Systemic effects - General population	Dermal	68.1 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	191 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	6.6 mg/m ³
Long term – Systemic effects - Workers	Inhalation	37.4 mg/m ³

CLEENOL

For a cleaner, safer world

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Long term – Systemic effects - General population	Oral	3.8 mg/kg bw/day
PNEC		
2,2'-(octadec-9-enylimino)bisethanol		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		160 ng/L
Freshwater sediment		1.692 mg/kg
Intermittent release (freshwater)		430 ng/L
Marine water		16 ng/L
Marine water sediment		169.2 µg/kg
Predators		2 mg/kg
Sewage treatment plant		1.5 mg/L
Soil		5 mg/kg
Diphenyl ether		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		455 ng/L
Freshwater sediment		92.6 µg/kg
Intermittent release (freshwater)		4.55 µg/L
Marine water		45.5 ng/L
Marine water sediment		9.26 µg/kg
Sewage treatment plant		10 mg/L
Soil		18.3 µg/kg
ethanol		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		960 µg/L
Freshwater sediment		3.6 mg/kg
Intermittent release (freshwater)		2.75 mg/L
Marine water		790 µg/L
Marine water sediment		2.9 mg/kg
Predators		380-720 mg/kg
Sewage treatment plant		580 mg/L
Soil		630 µg/kg
Sodium p-cumenesulphonate		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		100 µg/L
Freshwater sediment		372 µg/kg
Intermittent release (freshwater)		1 mg/L
Marine water		10 µg/L
Marine water sediment		37.2 µg/kg
Sewage treatment plant		100 mg/L
Soil		16 µg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

CLEENOL

For a cleaner, safer world

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Ensure that eyewash stations and safety showers are located within easy reach.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally


Use only UKCA marked protective equipment.

Respiratory Equipment

Type	Class	Colour	Standards
No special when used as intended.			


Skin protection

Recommended	Type/Category	Standards
Dedicated work clothing should be worn.	-	-




Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Butyl	0,3	> 120	EN374-2, EN374-3, EN388



Eye protection

Type	Standards
Safety glasses	EN166



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Blue

Odour / Odour threshold

Of perfume

pH

-

pH in solution

2 - 3 (10%)

Density (g/cm³)

-

Relative density

1.06 (20 °C)

Kinematic viscosity

Testing not relevant or not possible due to the nature of the product.

Dynamic viscosity

700 - 1500 poise cm³/g (20 °C)

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

Testing not relevant or not possible due to the nature of the product.

Vapour pressure

Testing not relevant or not possible due to the nature of the product.

Relative vapour density

Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards

Flash point (°C)

29

Flammability (°C)

The material is ignitable.

Auto-ignition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

Solubility in water

Very soluble

n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

Other physical and chemical parameters

No data available.

Oxidizing properties

Testing not relevant or not possible due to the nature of the product.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Mechanical influences (e.g. Shock, pressure, impact, friction). Fire, sparks or other ignition sources.

Storage in the open is not recommended.

10.5. Incompatible materials

Bases

Combustible materials

10.6. Hazardous decomposition products

Thermal decomposition may produce corrosive vapours.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

Endocrine disrupting properties

Not applicable.

Other information

None known.

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

12.2. ▼ Persistence and degradability

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

Not applicable.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 3 - Flammable

HP 8 – Corrosive

HP 14 – Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.







EWC code

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es) Label: 8+3 Classification code: CF1	14.4 PG*	14.5 Env**	Other information:
ADR	UN2920	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (2,2 ¹ -(octadec-9- enylimino)bisethanol)	Transport hazard class: 8 Label: 8+3 Classification code: CF1  	II	Yes	Limited quantities: 1 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN2920	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (2,2 ¹ -(octadec-9- enylimino)bisethanol)	Transport hazard class: 8 Label: 8+3 Classification code: CF1  	II	Yes	Limited quantities: 1 L EmS: F-E S-C See below for additional information.
IATA	UN2920	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (2,2 ¹ -(octadec-9- enylimino)bisethanol)	Transport hazard class: 8 Label: 8+3 Classification code: CF1  	II	Yes	See below for additional information.

* Packing group

** Environmental hazards

Additional information

Although this product is environmentally hazardous, the environmentally hazardous substance mark has been omitted as the product is supplied in packaging with a maximum quantity of 5 L / 5 kg.

ADR / See Table A, Section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.

People under the age of 18 shall not be exposed to this product.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

E1 - ENVIRONMENTAL HAZARDS, Qualifying quantity (lower-tier): 100 tonnes / (upper-tier): 200 tonnes

Labelling of contents according to Detergents Regulation (EC) No 648/2004

15% - 30%

· Non-ionic surfactants

5% - 15%

· Anionic surfactants

Additional information

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents as retained and amended in UK law. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Sources

The Management of Health and Safety at Work Regulations 1999.

The Health and Safety at Work etc. Act 1974 Regulations 2013.

Regulation (EC) No 648/2004 on detergents as retained and amended in UK law.

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

H302, Harmful if swallowed.

H314, Causes severe skin burns and eye damage.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

PC 35 = Washing and Cleaning Products (including solvent based products)

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

▼ The safety data sheet is validated by

Regulatory Chemist

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en